

MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 10/25/04

SECTION I

MANUFACTURERS NAME

SUNCOATINGS, INC

STREET ADDRESS

12290 73RD CT. N.

CITY, STATE, AND ZIP CODE

LARGO, FL 33773

EMERGENCY TELEPHONE NUMBER

1-800-247-9691

PRODUCT CLASS

ACRYLIC LATEX

MANUFACTURES CODE IDENTIFICATION

SM-3080

TRADE NAME

BLUE LATEX TRAFFIC PAINT

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
ETHYLENE GLYCOL CAS # - 107-21-1	1%	50		3.2%	.10MMHG
CAS #-					
CAS #-					
CAS #-					
CAS #-					

ADDITIONAL INFORMATION-

Hazardous Materials Identification System (HMIS)

Health
1

Flammability
0

Reactivity
0

Personal Protection
B

SECTION III – PHYSICAL DATA

BOILING RANGE: 379 °F - 401°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIR

EVAPORATION RATE FASTER SLOWER, THAN
ETHER PERCENT VOTILE BY VOLUME 100 % WEIGHT PER GALLON
BY VOLUME 9.00 LBS

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - NA

FLASH POINT- 232°F Minimum

EXTINGUISHING MEDIA-

CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPOLSION HAZARDS-
TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED

SPECIAL FIRE FIGHTING PROCEDURES-

WEAR SELF CONTAINED BREATHING APPARATUS.

WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

SECTION V – REACTIVITY DATA

STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE-NONE ESTABLISHED

EFFECTS OF OVEREXPOSURE-INHALATION OF VAPORS IN POORLY VENTILATED MAY CAUSE HEADACHE OR DIZZINESS. SKIN ABSORPTION SHOULD NOT BE A PROBLEM. DIRECT CONTACT MAY CAUSE EYE IRRITATION.

EMERGENCY FIRST AID PROCEDURE-REMOVE TO FRESH AIR. WASH EXPOSED AREAS WITH SOAP AND WATER. FLUSH EYES WITH COPIOUS AMOUNTS OF WATER IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: IF APPLIED BY SPRAYING, PARTICLE MASK SHOULD BE USED TO AVOID INHALATION OF ATOMIZED PAINT.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GLASSES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: N/A

SECTION IX – REGULATORY INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN OR CLOTHING. KEEP CONTAINER CLOSED. WASH THOROUGHLY AFTER USING.