

**CAN BE USED ON:**

- Masonry
- Stucco
- Wood
- Galvanized Metal

**PRODUCT ADVANTAGES:**

- 100% acrylic for best adhesion
- Gives mildew-resistant coating
- Very low odor
- Zero VOC

**THE LASTING BEAUTY OF GRANDEUR INSPIRED DÉCOR®** evokes the glamour and splendour of a luxury resort, a manor home on the French Riviera, and any space that aspires to elegant décor. Its thick, buttery finish spreads evenly and beautifully. Grandeur Inspired Décor provides a brilliant range of decorator colors and finishes that restore and beautify any space.

**READ AND FOLLOW ALL DIRECTIONS:** Surfaces must be clean, dry, and sound; contaminants such as dirt, dust, grease, wax, oils, soap film, rust, mold & mildew, bond breakers, curing compounds, and loose, peeling paint must be removed before priming or painting. Repair holes & cracks with appropriate patching material.

**PRECAUTION:** Do not freeze. Wear protective clothing and eyewear during application of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperature above 100°F (37°C). Do not use in drinking water or food systems.

**PREPARING NEW UNPAINTED SURFACES:** Drywall: Prime with latex or acrylic drywall primer/sealer. Wood: Prime with latex wood undercoater. Plaster: Prime plaster with latex or acrylic primer/sealer. Concrete, Masonry, Brick & Stucco: Allow to fully cure and dry throughout per manufacturer directions. Surface pH must be less than 10.0. Remove loose material. Roughen smooth, slick concrete by acid etching or sand sweeping, following all manufacturers' directions. Rinse thoroughly with water and allow to dry. Prime with masonry primer. Concrete Block / CMU: Fill block with latex block filler. Metal: Remove rust and machine oils, and prime with primer appropriate for the metal being painted according to manufacturer instructions.

**PREPARING PREVIOUSLY PAINTED SURFACES:** Dull glossy areas by lightly sanding. Wash to remove sanding dust, loose paint, and other contaminants. Rinse thoroughly with water and allow drying. Spot prime bare areas with primer specified above.

**TINTING:** Tint appropriate tint base with SUN colorants. Factory-tinted colors cannot be re-tinted unless indicated on label as tintable. Available in white, pastel, light, deep, and masstone tint base.

**APPLICATION:** Mix thoroughly before use. Apply at a rate of 400 sq ft/gal (10m<sup>2</sup>/l) with a brush, roller or airless sprayer. Brush: use appropriate, premium latex paint brushes. Roller: use a 1/4"-3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces and a 3/4"-1" nap cover for rough surfaces. Airless spray: use a .015"-.017" tip, and adjust pump pressure as needed. Coverage: Actual coverage may vary depending on substrate and application method. For best hiding, use appropriate grey basecoat or tint primers towards finish coat color. Certain deep, bright colors (red, orange, yellow, etc.) require multiple coats for even coverage. Thinning: Thinning is not required. Temperature: Do not apply when the surface or air temperature is below 45°F (7.5°C). Provide good ventilation and warm room temperatures while drying. Dry time: Dries to touch in less than 1 hour @ 77°F (25°C) and 50% R.H., and may be recoated in 2-4 hours. Temperature, humidity, film thickness, surface porosity, and ventilation can affect dry time.

**TOOL & APPLICATOR CLEANING:** Clean tools & applicators immediately with warm, soapy water. Dried paint may require cleaning with Mineral spirits (paint thinner).

**WALL CARE:** Allow 7 days after applying before washing walls. Use nonabrasive, mild detergent and cellulose sponge or warm baby wipes. Do not lean objects against freshly painted surfaces.

**SEE MSDS FOR ADDITIONAL INFORMATION.**

**TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS**

Weight Per Gallon	10.51 lbs.
Solids by Weight	47.4%
Solids by Volume	34.3%
Gloss Reading at 60 °	10-20
Viscosity (ASTM D-2697)	95-100 KU
Film Dry Thickness	2.0 mil
Combustible Solvents	None
Consistency	Brush, spray or roller
Suggested Coverage (varies per substrate)	300-400 SFPG
Cure Time (50% Relative Humidity, 70°F)	30 min.
Full Cure (50% Relative Humidity, 70°F)	1-2 hours
Application Temperatures	50° - 110°F
Clean-up Tools	Water

**APPROXIMATE SHIPPING WEIGHTS:** Note - all weights include container.

1 gallon (3.8L)	12 lbs.
(4) 1 gallon containers/case	48 lbs.
5 gallons (18.9L)	60 lbs.
55 drums (208.2L)	660 lbs.

**FIRST AID:** If swallowed, gently wipe or rinse the inside of the mouth with water. Water may be given if person is alert. Do NOT induce vomiting. Get medical attention immediately. If skin/eye contact occurs, flush the affected areas with warm water for at least 15 minutes. Remove contact lens. A mild soap may be used on skin if available. If inhaled, remove from area to fresh air. If breathing is difficult, get medical attention immediately. Take MSDS or label information.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**CAUTION!**

**HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.**

**CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).** WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

**VOC/VOS:** Contains less than 0 g/l

Water/Agua	CAS # 7732-18-5
Latex Polymer	CAS # Mixture
Titanium/Titanio	CAS # 13463-67-7
Calcium Carbonate	CAS # 1317-65-3

Product is asbestos free.

**WARRANTY AND DISCLAIMER:** For limited warranty and disclaimer information, contact the Sun Paints & Coatings corporate office at 1-800-247-9691.

